


Male coupling with gasket for SPIRAL ducts

NSL



Dimensions



Description

NSL male couplings allow connecting SPIRAL round ducts or round plain ducts with inner joints. The piece is installed by pressing both ends into the ducts to be joined, up to the stop in the middle of the male coupling. Next, the male coupling needs to be fastened to both ducts with self-drilling screws or rivets. As a result of the double EPDM rubber gasket, the product meets requirements for air tightness class D according to EN 12237.

Available materials - Product code example

- NSL-... - galvanized steel sheet
- NSL-K-... - 1.4301/304 stainless steel sheet
- NSL-K-...- 316L - 1.4404/316L stainless steel sheet, molybdenum-enriched
- NSL-A-... - AW-1050A H24 aluminium sheet
- NSL-CU-... - M1E z4 copper sheet
- NSL-ZM-... - ZM310 coating (only up to a diameter of Ød1 = 500mm)

Product code example

Product code: NSL - aaa

type _____
 Ød _____

Ød_{nom} [mm]	R [mm]	Weight [kg]
80	8	0.10
100	8	0.12
125	8	0.15
140	8	0.17
150	8	0.18
160	8	0.19
180	8	0.21
200	8	0.24
224	8	0.27
250	8	0.30
280	8	0.35
300	8	0.36
315	8	0.38
355	8	0.58
400	8	0.65
450	8	0.95
500	8	1.05
560	8	1.45
600	8	1.55
630	8	1.60
710	10	2.75
800	10	2.10
900	12	3.45
1000	12	5.70
1120	12	6.40
1250	12	7.15
1400	12	4.75
1500	12	5.10
1600	12	5.40