





### Applications

The clamps are designed for quick and reliable mounting and connection of various round ventilation system components. The clamps facilitate the installation and removal of fans for maintenance and cleaning.

#### Design

**C** series clamps are made of stainless steel (C series) or galvanized steel (C.. Z.) strips. The clamps are tightened with screws.

- **CB** series clamps are the quick detachable clamps of stainless steel with the swing screw of stainless steel. The clamps are tightened with screw.
- **CBR 3000** series clamps are the band clamps in a plastic covering (roll 30 m x 9 mm x 0.8 mm). Locking devises set SU 50 (50 pcs) is supplied separately. Using a band of the worm drive clip of the required length and locking device you have the required diameter clamp. The clamps are tightened with screws.

Tin snips are everything you need to have the


required length clamp as the plastic casing has a special design and marking.

# Application:

- 1. Bend the clamp edge.
- 2. Fix the bent edge of the band into the band holder.
- 3. Turn the band holder till the mark of the required diameter on the casing.
- 4. Cut the band away as applicable for the casing.
- 5. Fix the locking device on the clamp.

#### **Overall dimensions:**

Dimensions [mm]		
ØD	Н	
90-110	9	
110-130	9	
120-140	9	
140-160	9	
150-170	9	
190-210	9	
240-260	9	
300-330	9	
	ØD 90-110 110-130 120-140 140-160 150-170 190-210 240-260	





Easy locking device for CB and CBR clamps.

# **Overall dimensions:**

Туре	Dimensions [mm]		
	ØD	Н	
CB 60-110	60-110	9	
CB 60-135	60-135	9	
CB 60-165	60-165	9	
CB 60-180	60-180	9	



Series	
C CB CBR	

Diameter [mm]	
100; 125; 150; 160; 200; 250; 315 60-110; 60-135; 60-165	